





SUC 208



Dual Seals

Unit No.	Shaft Dia.		Dimensions (in)									Basic load rating		Mass	
	d		Dimensions (mm)									lbf / N			
	in	mm	D	B	C	S	S1	G	ds	d4	h	dynamic Cr	static C0r	kg	lbs
SUC 208-24	1-1/2		3,1496	1,9370	0,8268	0,748	1,1890	0,315	5/16-24	2,079	0,177	4632	3034	0,69	1,52
208-25	1-9/16													0,66	1,46
208		40	80	49,2	21	19,0	30,2	8,0	M8 X 1	52,81	4,5	20604	13496	0,65	1,43
SUC 209-26	1-5/8		3,3465	1,9370	0,8661	0,748	1,1890	0,315	5/16-24	2,307	0,193	5888	3450	0,80	1,76
209-27	1-11/16													0,76	1,68
209-28	1-3/4		85	49,2	22	19,0	30,2	8,0	M8 X 1	58,60	4,9	26192	15345	0,71	1,57
209		45												0,70	1,54
SUC 210-30	1-7/8		3,5433	2,0315	0,9055	0,748	1,2835	0,354	5/16-24	2,449	0,232	6320	3885	0,87	1,92
210-31	1-15/16													0,82	1,81
210		50	90	51,6	23	19,0	32,6	9,0	M8 X 1	62,20	5,9	28112	17280	0,80	1,76
210-32	2													0,77	1,69
SUC 211-32	2		3,9370	2,1890	0,9440	0,874	1,3150	0,354	3/8-24	2,756	0,236	7808	4914	1,23	2,71
211-34	2-1/8													1,18	2,60
211		55	100	55,6	24	22,2	33,4	9,0	M8 X 1	70,00	6,0	34732	21859	1,08	2,376
211-35	2-3/16													1,06	2,34
SUC 212-36	2-1/4		4,3307	2,5630	1,024	1,000	1,5630	0,394	3/8-24	3,031	0,244	9440	6071	1,66	3,66
212		60												1,53	3,37
212-38	2-3/8		110	65,1	26	25,4	39,7	10,0	M10 X 1,25	76,99	6,2	41992	27008	1,51	3,33
212-39	2-7/16													1,44	3,17

Other sizes could be available upon request. Minimum quantity may apply.  
Please refer to page 45 for setscrew maximum torque informations.